

# PC DISTRIBUTION AMPLIFIER

FOR VIDEO PROJECTION – RGB MONITORING – CONFERENCE ROOM – PROCESS CONTROL – INDUSTRIAL ENVIRONMENT

## DUAL VGA SPLITTER

Ref : DVS

- **Input :**  
PC, Up to 1600 x 1200 (75 Hz)
- **2 Outputs**



### REFERENCE :

- DVS

### FEATURES :

- Ultra-Low cost
- Metal enclosure
- Very compact

### DESCRIPTION :

The **DUAL VGA SPLITTER** takes the computer's video signal and displays it on up to 2 monitors. The same image is displayed on both monitors. The splitter provides a fast and flexible solution for Presentations, Test Bench facilities or RGB distribution such as Remote Monitoring, Education Facilities, etc...

### TECHNICAL SPECIFICATIONS :

<b>INPUTS</b>	<ul style="list-style-type: none"><li>- Accepts signals from any PC (VGA to UXGA)</li><li>- RGB S, RGBHV, (RGB 0,7V analog).</li><li>- SYNC. : (Hi-Z), COMPOSITE, 5V TTL, H &amp; V separated, 5VTTL</li><li>- Line frequency from 15 kHz to 95 kHz</li><li>- Frame frequency from 40 Hz to 150 Hz</li><li>- Video bandwidth : 200MHz</li><li>- Connector : 15 Pin HD male</li></ul>
<b>OUTPUTS</b>	<ul style="list-style-type: none"><li>- 2 separate and buffered outputs : RGBS, RGBHV</li><li>- RGB : 0,7V p/p : COMPOSITE and H &amp; V Sync. : 5V TTL Boosted</li><li>- Impedance : RGB = 75 Ω</li><li>- Connectors : 15 pin HD female</li></ul>
<b>DIMENSIONS</b>	<ul style="list-style-type: none"><li>- D73 x W121 x H43 mm</li><li>- D2,87" x W4,76" x H1,69"</li></ul>
<b>WEIGHT</b>	0,7 kg / 1,54 lbs
<b>POWER SUPPLY</b>	External (wall mount) <u>Inputs</u> : <ul style="list-style-type: none"><li>- 110 V/ 60 Hz (US), or</li><li>- 220 V/ 50 Hz (EUR), or</li><li>- 230 V/ 50 Hz (UK). Available</li></ul> <u>Output</u> : +9 Vdc/0,85 W
<b>SUPPLIED WITH</b>	1 x Power Supply
<b>WARRANTY</b>	1 year warranty on Parts & Labor, back to the factory

### ACCESSORIES REFERENCES (Optional) :

- 10016 : HD 15 M/F Cable (3m - 10ft)
- 10017 : HD 15 M/F cable (6m – 20ft)
- 10019 : HD 15 M/F cable (10m – 33ft)
- 10074 : HD 15 M/F cable (20m – 66ft)
- 10022 : HD 15 M/F cable (6m – 20ft)
- 10076 : HD 15 M/F cable (10m – 33ft)
- 10084 : HD 15 M/F cable (20m – 66ft)
- 10042 : Set of MAC RGBS/VGA cable adapter
- 10045 : Set of MAC HV/VGA cable adapter

[www.analogway.com](http://www.analogway.com)

SB / 5 Sept. 2003