

SCART VIDEO BOOSTER

FOR EUROPE SCART APPLICATIONS ONLY – TO DISPLAY 1 SOURCE ON 4 TV DISPLAYS TELECONFERENCE – VIDEO PRESENTATION – SECURITY

QUAD TV BOOSTER™ Ref. QTVB-4

- 1 A/V Input
- 4 A/V Outputs

REFERENCE :

- QTVB -4

FEATURES :

- SCART connection (Europe)
- Audio Stereo
- Long distance application
- Synchronisation switch



DESCRIPTION :

The **QUAD TV BOOSTER™** is available with 4 output channels. It allows to drive any video signal and to display your source simultaneously on 4 Tv supports, video projectors or video recorders (RGB/S or Composite). This Interface is very easy to use. Buffered Stereo Audio is also provided. In addition, the Quad TV Booster™ Supports ALL kinds of SCART cables.

TECHNICAL SPECIFICATIONS:

INPUTS :

On SCART connector :

- RGB + Sync. = 0.7 Vp/p + 0.3 Vp/p (75 Ω)
- Composite (PAL/SECAM/NTSC) : 1 Vp/p (75 Ω)
- Audio : + 12 dBm (3 Vrms) / 47 KΩ
- Composite / RGB switch for input signal type connection

On Jack 3.5 connector :

- Audio : +12 dBm (3 Vrms / 47 K Ω)
- STD>< switch for selection of straight or crossed cable (Pin 19/20)
Video loopthrough = 15 MHz (-3 dB)
Audio loopthrough = DC at 100 kHz (-3 dB)

OUTPUTS :

On SCART connector :

- RGB + sync.= 0.7 Vp/p + 0.3 Vp/p (75 Ω)
- Composite (PAL/SECAM/NTSC) : 1 Vp/p (75 Ω)
- Audio : +12 dBm (3Vrms) / 47 K Ω
- STD/ >< switch for selection of straight or crossed cable (Pin 19/20)

Each video and audio output has its own booster.

DIMENSIONS :

- D105 x W330 x H50 mm
D 4.1" x W12.87" x H 1.95"

WEIGHT :

1.2 kg / 2.6 Lbs

POWER SUPPLY :

220 Vac / 15 watts

SUPPLIED WITH : 1 x AC Power cable

WARRANTY : 3 years warranty on Parts & Labor back to the factory

ACCESSORIES REFERENCES (Optional) :

- 10000 : Scart Cable (1,5m – 6ft)
- 10001 : Scart Cable (6m – 20ft)
- 10002 : Scart Cable (8m – 26ft)
- 10003 : Scart Cable (10m – 33ft)
- 10004 : Scart Cable (20m – 66ft)
- 10005 : RCA + Jack to Scart cable (2,8m / 9ft)
- 10006 : Scart to RCA + jack cable (2,8m / 9ft)