

# CVD 5006

## RGBHV SWITCHER

6 In, 1 Out



### Technical Specifications

#### INPUT OVERVIEW

Signals . . . . . Analog RGBHV, RGBS, RGsB, RsGsBs  
Connectors. . . . . (30) BNC Female  
Video Impedance . . . . . 75 Ohms  
Video Level . . . . . 0.5 – 1.5 Vpp  
Sync Impedance . . . . . > 10K Ohm  
Sync Level . . . . . Analog / TTL / 0.5 - 5.0 Vpp  
Sync Polarity. . . . . + / -

#### OUTPUT OVERVIEW

Signal . . . . . Follows Input  
Connectors. . . . . (5) BNC Female  
Video Impedance . . . . . 75 Ohms  
Video Level. . . . . Follows Input  
Sync Impedance . . . . . 75 Ohms  
Sync Level . . . . . TTL  
Bandwidth . . . . . 250 MHz

#### CONTROL

RS232, 3 Position, Terminal Block  
Front Panel Keypad  
RF Remote (Optional)

#### DISPLAY

Power On Indicator  
Seven-Segment Channel Readout

### Physical Specifications

Dimensions . . . . . 1U High, 1 Rack Wide  
(inches) . . . . . 1.75 H x 17.00 W x 9.50 D  
(cm) . . . . . 4.45 H x 43.18 W x 24.13 D  
Enclosure. . . . . Aluminum, Black, Texture Finish  
Weight . . . . . 5.7 lbs / 2.6 kg  
Input Voltage . . . . . 110 or 220 VAC, 60/50 Hz, Internal  
Power Dissipated. . . . . 7 Watts

### Accessories

CVD 0181 . . . . . Rack Mount Ears (included)  
CVD 0014. . . . . Power Cord (included)