

# CVD 5906

## VGA SWITCHER

6 In, 1 Out



### Technical Specifications

#### INPUT OVERVIEW

Signals . . . . . Analog RGBHV, RGBS, RGsB  
Connectors . . . . . (6) 15-Pin HD Female  
Video Impedance . . . . . 75 Ohms  
Video Level . . . . . 0.5 - 1.5 Vpp  
Sync Impedance . . . . . 10K Ohms  
Sync Level . . . . . Analog / TTL  
Sync Polarity . . . . . + / -

#### OUTPUT OVERVIEW

Signal . . . . . Follows Input  
Connector . . . . . (1) 15-Pin HD Female  
Video Impedance . . . . . 75 Ohms  
Video Level . . . . . Follows Input  
Sync Impedance . . . . . 75 Ohms  
Sync Level . . . . . TTL  
Bandwidth . . . . . 250 MHz

**CONTROL** . . . . . RS232 (9-Pin D-Sub Female Connector)  
Front Panel Keypad  
RF Remote (Optional)

**DISPLAYS** . . . . . Power On Indicator  
Seven-Segment Channel Readout

### Physical Specifications

Dimensions . . . . . 1U High, 1/2 Rack Wide  
(inches) . . . . . 1.75 H x 8.50 W x 6.00 D  
(cm) . . . . . 4.45 H x 21.59 W x 15.24 D  
Enclosure . . . . . Aluminum, Black, Texture Finish  
Weight . . . . . 1.5 lbs / 0.68 kg  
Input Voltage . . . . . 110 or 220 VAC Wall Mount,  
12 VAC, 1A, UL  
Power Dissipated . . . . . 7 Watts

### Accessories

CVD 0185 . . . . . Rack Mount Ears (optional)  
CVD 0003 . . . . . Power Supply (included)