

# Evenroll Rope-and-Pulley

*Simple and economical for large audiences.*

When a large, roller-operated screen is required, choose the EVENROLL. Sizes to 30' x 30', installs easily to wall or ceiling. Rope-and-pulley operation utilizes nylon marine pulleys and flanged spools for smooth operation, with no mistracking cords. Select fiberglass matt white or glass beaded viewing surface.

If screen installs in center of stage and operating cords are to extend to wall, be sure to indicate distance from edge of screen to wall and request extra cord, double wheel pulley, and cord cleat on wall plate. Batten and roller are 18" wider than viewing surface (9" on each side). Screen depth is 6" (front to back). Maximum screen height when closed is 14".

## *System Options*

- **Extra Drop**—Up to 30' overall height, either white or black (white is standard).
- **Black Masking Borders**—Available in 2" widths.
- **Wall Mounting Brackets**—Extend screen 12" from wall. Formed of 1/4" strap steel. Divide screen width by 5 for proper number.

*Flanged aluminum spools at ends of roller contain operating cords, preventing them from tracking into the viewing surface. Nylon marine pulleys operate smoothly and silently. Steel housings prevent cords from slipping off pulleys.*



Size H x W	Ship Wt. (lbs.)	Size H x W	Ship Wt. (lbs.)
7' x 14'	70	15' x 20'	270
11' x 14'	75	20' x 20'	280
14' x 14'	80	12' x 24'	350
8' x 16'	80	18' x 24'	380
12' x 16'	95	24' x 24'	425
16' x 16'	110	14' x 28'	450
9' x 18'	185	21' x 28'	475
13'6" x 18'	215	15' x 30'	450
18' x 18'	230	22'6" x 30'	500
10' x 20'	260	30' x 30'	550