

LPV-10 Transmitter/Translator

Video/Data Transmitter, Digital Service (Analog Compatible)



The new EMCEE LPV-10 is the Up-Converter/Driver section of the new LPV Series™ Transmitter/Translator product line. It provides a 1 Watt, VHF Band 1/3 output, and it represents the highest evolution in a low power VHF triple conversion design for a very low power transmitter or translator using LDMOS technology. Inherently low distortion minimizes the need for extensive corrective circuitry and provides for excellent performance in lower power digital and analog applications. Broadband circuitry complemented by modular packaging enables simplified maintenance with reduced spare requirements and at the same time provides a path for channel flexibility. A new generation, EMCEE designed, low phase-noise synthesizer/local oscillator chain provides built-in channel agility together with GPS/NAVSTAR or LORAN synchronizing capability for high precision frequency control and co-channel interference reduction. Front panel monitoring of all internal voltages and forward power is provided in an easy to read LCD display. Web based control interfacing for critical transmitter functions and monitoring is available via the rear chassis connections. The LPV Series is the perfect choice for transition into digital service and for very low power analog.

Features

- High Reliability
- Modular Design
- Analog & Digital Compatible
- Fully Synthesized
- Built-In Web Based Remote Control
- Minimum Operator Adjustments

Benefits

- LDMOS Technology
- Ease of Maintenance
- Versatility
- Built-in Channel Agility
- Ease of Management
- Simplified Operation

SERVING THE BROADCAST INDUSTRY SINCE 1960

SPECIFICATIONS – LPV SERIES TRANSMITTERS

Model LPV-10

<i>ANALOG (VISUAL) SERVICE</i>		<i>DIGITAL SERVICE</i>	
Output Power	2.5 Watts Peak Visual Power w/-10dB Aural Carrier	Output Power	1 Watt Average ATSC .5 Watts DVB-T
Emission	5M75C3F	Emission	6M00D7W
Color Transmission	NTSC, PAL, SECAM	Modulation Mode	QPSK/16/64/256QAM, 8 OR 16 VSB
Output Frequency	Band 1/3 54-88/170-230 MHz	Output Frequency	Band 1/3 54-88/170-230 MHz
Frequency Stability	±1 KHz	Frequency Stability	±1 KHz, <1Hz with GPS input
Spurious Products ¹	-60 dB	Spectral Mask ¹ Per FCC	-37dB @ channel edge, -100 dB @ ±6 MHz Ref Channel edge below Average Power (Watts/5.4 MHz)
Intermodulation (IM3)	<-56dB	Spurious Products	<-60dB
Differential Phase	±2°	Envelope Delay	±5ns
Differential Gain	3%	Frequency Response	±0.5dB
Low Frequency Linearity	3%	Error Vector Magnitude	≤3%, SNR >30dB
Envelope Delay	Better than FCC 73.687 (a) (3)	Output Power Stability	±0.3dB
Sideband Response	Better than FCC 74.936 (b)	Digital Signal to Noise	34dB
Frequency Response ¹	±0.5 dB	Hum & Noise	<-60dB
Output Power Stability	±0.3dB	Phase Noise (Synth)	≤-104dBc/Hz @ 20 KHz
RF Regulation	2%	Harmonic Output	<-60dB
Signal to Noise	55dB	IF Input Level	-5 to -15 dBm
Hum and Noise	-55 dB	Input Impedance	75 Ohm/BNC, 44Mhz
Phase Noise (Synth)	-100 dBc/Hz @ 10 KHz	Output Impedance	50 Ohm/N
K Factor (2T)	2%	GENERAL/MECHANICAL CHARACTERISTICS	
ICPM	3°	(Specific to Both <u>Analog & Digital</u> Service)	
Harmonic Output	-65dB	Operating Temperature, Alt.	0° to +50°C, 10,000 Ft. AMSL
Input Impedance (Composite)	75 Ohm/BNC	Maximum Relative Humidity	95%
Output Impedance	50 Ohm Type N	Weight/Dimensions	16 lbs. 1.75"Hx19"Wx22.5"D
ELECTRICAL CHARACTERISTICS		Power Requirements	85~264 VAC ±15%, 47~63 Hz
<u>ANALOG</u> (AURAL) SERVICE		Power Consumption/PF	60 Watts/0.98
Output Power	-10 dB Ref. to Visual		
Emission	250KF3E		
Frequency Tolerance	NTSC +4.5 MHz ±100 Hz CCIR+5.5 & 6.5 MHz ±100 Hz		
Audio Distortion	1.0%		
FM Noise	-60 dB		
AM Noise	-60dB		
Frequency Response	±1 dB		
Deviation	25KHz Mono, 50 KHz Stereo or per CCIR Requirements		

¹Measured with Output Filter
Specifications Subject To Change

U.S. Sale Subject To FCC Type Approval