



VP-6xIN

1:6 COMPUTER GRAPHICS VIDEO DISTRIBUTION AMPLIFIER



SPECIFICATIONS

INPUTS:	1 XGA on an 15-Pin HD F connector
OUTPUTS:	6 XGA on 15-Pin HD F connectors
MAX. OUTPUT LEVEL:	1.7Vpp
BANDWIDTH:	500MHz.
DIFF. GAIN:	0.09%
DIFF. PHASE:	0.01°.
K-FACTOR:	<0.05%
S/N RATIO:	72dB
CONTROLS:	0 to +10dB EQ.
COUPLING:	DC
POWER SOURCE:	100-240VAC, 50/60Hz, 18VA
DIMENSIONS:	19 inch (W), 4 inch (D), 1U (H) rack mountable.
WEIGHT:	2.7kg (6lbs) approx.
ACCESSORIES:	Power cord

DESCRIPTION

The VP-6xIn is a high performance distribution amplifier for computer graphics video signals with resolutions ranging from VGA through UXGA and higher. It takes one input, provides correct buffering and isolation and distributes the signal to six identical outputs.

- High Bandwidth - 500MHz (-3dB)
- HDTV Compatible
- ID Bit Control
- EQ (peaking) Control
- Standard 19" Rack Mount Size - 1U. Rack "ears" included.

