

The Biggest Thing in LCD Monitors

LCD-1700V LCD-1700VR LCD-1703VRZ



LCD-1700V



LCD-1700VR
in 19" Rack Mount Kit



LCD-1703VRZ
in 19" 1 RU Rack Mount

Active Matrix 17" Color LCD Monitors

• RS-232 feature allows external devices to control the monitor through the serial port.

- LCD-1703VRZ, 17" LCD color monitor in standard 19" rack mount kit
 - Occupies 1 Rack Unit
 - Monitor automatically turns ON/OFF when tilted up/down
 - Rear mounting bracket extends from 24" to 30"

- Hot key allows toggling between video, S-Video, component, PC modes
- PIP: Picture in picture capability with front toggle key
- On-screen display for: brightness, contrast, back light, hue, volume
- Front control keys for power, menu, auto, +/-, up/down
- For color and B&W applications
- Low power consumption
- Case made of durable ABS plastic
- Active matrix technology allows wide viewing angle
- Active matrix technology eliminates distortion
- LCD-1700V includes built-in removable desk stand
- LCD-1700V has built-in interface for wall or wall mounting VESA 100mm FPMPMI compliant
- Response Time: 35/20ms (rising/falling)

Optional Accessories

- | | |
|----------|--|
| DC-1500 | Factory approved car cord |
| HM-400 | Under-cabinet hinge mount |
| WM-30 | Wall mount bracket (fixed) |
| WM-302 | Wall mount with swing arm & 4-way adjustable |
| WMC-1720 | Ceiling mount |



HM-400



WM-302

- Display: 17.0" TFT LCD active matrix
- Back Light: Built-in (CCFT)
- Input Signal: Composite NTSC/PAL (auto switching), S-Video, component, DVI, Analog RGB
- Resolution: SXGA 1280(H) x 1024(V)dots
- PC compatibility: IBM / MAC compatible
- Dot Pitch: 0.264(H) x 0.264(V)mm
- Brightness rating: 350 cd/m² (Nit)
- Colors: 16.7M
- Contrast Ratio: 500:1
- Number of Pixels: 1,310,720 dots
- Viewing angle L/R/T/B: 85/85/85/85 degrees
- Pixel Configuration: Stripe
- Input Signal Level: 1.0V P-P (positive) 75 Ohm
- Speakers: 8 ohms, 2W, 28 x 40mm oval type x 2
- Stereo Amplifier: 2 W x 2 @ 10% THD, 100 mV
- LCD-1700V: Dimensions w/o desk stand (WHD): 426 x 376 x 67mm / 16.8" x 14.8" x 2.6"
- LCD-1700V: Dimensions w/ desk stand (WHD): 426 x 432 x 162mm / 16.8" x 17" x 6.4"
- LCD-1700VR: Dimensions (WHD): 19" x 14" x 2.5"
- LCD-1703VRZ: Dimensions (WHD): 19" x 1.75" x 24"
- Actual visible screen size (WH): 338 x 270 mm / 13.3" x 10.6"
- Operating temperature: 50~104°F or 10~40°C
- Power Requirement: Regulated 12VDC, 4A, negative ground
Part No. DC-1500 required for use in vehicles
- Power Consumption: LCD-1700V: 45 W (max), 3 W (power saving off mode)
LCD-1700VR/ 1703VRZ: 48 W (max), 3 W (power saving off mode)
- Includes switching power supply: 100 ~ 240VAC (auto-sensing), 50 ~ 60Hz, 1.2A
- Rear Terminal Connections: BNC video IN/OUT jacks, 3.5 stereo audio IN jack, RCA video IN, RCA L/R audio IN, 2.1mm DC IN jack, S-Video jack, DVI (22 pin) w/ DVI /VGA cable, 3.5 mm RS-232 IN, 9-pin component IN
- LCD-1700V: Weight: Net: 7.3 kg. / 16 lbs. Gross: 9.5 kg. / 21 lbs.
- LCD-1700VR: Weight: Net: Est.7.4 kg. / 16.4 lbs Gross: 9.7 kg. / 21.4 lbs.
- LCD-1703VRZ: Weight: Net: 14.4 kg. / 13.8 lbs. Gross: 9.5 kg. / 21 lbs.

Touch Screen: order LCD-1700TS for model LCD-1700V
Touch screen not available for model LCD-1703VRZ