

For more information visit  
[www.vinten.com](http://www.vinten.com)

## Sales Offices

### CHINA

Room 1806, Hua Bin Building  
No. 8 Yong An Dong Li  
Jian Guo Men Wai Ave  
Chao Yang District  
Beijing, P.R.China 100022

t +86 10 8528 8748  
f +86 10 8528 8749

### FRANCE

171, Avenue des Grésillons  
92635 GENNEVILLIERS Cedex  
France

t +33 820 821 336  
f +33 825 826 181

### GERMANY

Gebäude 16  
Planiger Straße 34  
55543 Bad Kreuznach  
Germany

t +49 671 / 483 43 30  
f +49 671 / 483 43 50

### JAPAN

P.A. Bldg. 5F  
3-12-6 Aobadai  
Meguro-ku Tokyo 153-0042  
Japan

t +81 3 5456 4155  
f +81 3 5456 4156

### SINGAPORE

6 New Industrial Road  
#02-02 Hoe Huat Industrial  
Building  
Singapore 536199

t +65 6297 5776  
f +65 6297 5778

### UK

William Vinten Building  
Western Way  
Bury St Edmunds  
Suffolk IP33 3TB  
UK

t +44 1284 752 121  
f +44 1284 750 560  
Sales Fax +44 1284 757 929

### USA

709 Executive Blvd  
Valley Cottage  
NY 10989  
USA

t +1 845 268 0100  
f +1 845 268 0113  
Toll Free Sales: 1 888 2 Vinten

Protouch Systems | Protouch lightweight camera support



## VintenProtouch Lightweight Camera Support System



### Changes in Product Specification

Vinten reserve the right to alter specifications or change materials where absolutely necessary. All sizes shown throughout this brochure are approximate and colours shown are as accurate as modern reproduction methods will allow. No liability can be accepted for any variation.

© 2007 The Vitec Group plc

© VINTEN, VISION, VECTOR, QUICKFIX & QUICKFIT are registered trademarks of The Vitec Group plc.

QUALITY SYSTEMS APPROVED TO ISO 9001:2000  
Certificate No. 009508

V1/08/07

**Vinten**

simply perfection

ProtouchSystems | Protouch lightweight camera support

**Vinten**

simply perfection

[www.vinten.com](http://www.vinten.com)

## Vinten Protouch Systems: Introducing the Pozi-Loc Tripod

### Unrivalled torsional rigidity transferred from the award winning Vision Range

Picture quality relies as much upon the rigidity of the camera support as it does on the smoothness of the pan & tilt head and accuracy of the counterbalance. Protouch is unique because it includes the Pozi-Loc tripod synonymous with the Vision Range.

Vinten Pozi-Loc was designed to optimise rigidity without compromising operational essentials such as weight, reliability, maintenance and speed of set-up. This special edition Protouch black aluminium Pozi-Loc tripod completes the picture, making Protouch the best value high performance system on the market.

#### The importance of Vinten design.



The **Protouch** range has been introduced to appeal to those working in event videography and the corporate sector, enabling videographers to maintain a professional look and feel to their work whilst managing a tight budget.

The **Pro-10** and the **NEW Pro-6<sup>HDV</sup>** offer the perfect solution for supporting the ever-increasing range of professional DV camcorders from 2kg to 10kg.

The Protouch heads feature continuously variable fluid drag and the capacity to handle the smallest DV camcorder to today's generation of multi-purpose ENG format cameras. This ensures that these lightweight heads provide smooth movement and complete camera control for any application. Designed to be simple to use the Pro-6<sup>HDV</sup> and Pro-10 incorporate easy to adjust drag knobs and an illuminated levelling bubble for quick and convenient set up in low light situations.

**The Protouch range offers a truly professional alternative, backed by the Vinten brand.**

**NEW**  
The Pro-6<sup>HDV</sup> system includes a NEW system case featuring the U-Grip ergonomic interlock plastic handle



## Pro-6<sup>HDV</sup>

For the new generation of camcorders up to 6kg

Sideload system allows for rapid camera attachment, adjustment and removal.



3 levels of counterbalance plus zero position for extremely lightweight camcorders and easy to adjust pan and tilt drag.



Illuminated levelling bubble for quick and convenient set up in low light situations.



**Pro-6<sup>HDV</sup>** is available as an off the shelf head or incorporated into two lightweight systems with the Vinten Pozi-Loc tripod (see page 2), a branded black fabric system case (see page 3) and either the standard floor spreader or a new lightweight mid-level spreader that offers a much wider range of stable footprints for any location or terrain.

Continuously variable fluid pan and tilt drag and stepped counterbalance up to 6kg (13.2lbs) ensures that the Pro-6<sup>HDV</sup> head provides smooth movement and complete camera control.

- Pro-6<sup>HDV</sup>F System with floor spreader
- Pro-6<sup>HDV</sup>M System with mid-level spreader
- V4018-0001 Pro-6<sup>HDV</sup> pan & tilt head

## Pro-10

For larger cameras up to 10kg (22lb)



Illuminated levelling bubble for quick and convenient set up in low light situations.



The **Pro-10** camera support system is the perfect combination for the latest professional digital and ENG cameras. Providing exceptional value for money the system comprises of the Pro-10 pan & tilt head, Pozi-Loc two-stage tripod (see page 2), a floor spreader and soft case.

The Pro-10 head provides smooth control and movement through 360° of pan and +90° to -60° of tilt with continuously variable fluid drag.

- Pro-10DC System with floor spreader
- 3809-3 Pro-10 pan & tilt head

# Dolly

The **Protouch PD114 multi-purpose dolly** is an ideal optional accessory for any Protouch system. The lightweight and compact folding dolly is supplied with individual wheel locks and removable cable guards, making it ideal for studio and outside applications.

U005-103 Dolly



# Spreaders



A **spreader** is essential, it maximises stability, allowing the camera operator to utilise the full performance of the pan and tilt head.

The Protouch floor spreader offers the most stability and a generous amount of flexibility, but the terrain may be too rough and prevent its use. Therefore, a mid-level spreader can be the safest option to ensure stability and camera control in any situation.



The **new** lightweight mid-level spreader, suitable for both systems, allows individual telescopic adjustment of each leg and provides a wide range of stable footprints. The overall footprint is determined by a two position central selector allowing for an extremely small footprint for tight areas and a large footprint where conditions allow.

3818-3 Ground spreader  
V4032-0001 Mid-level spreader (with 3 rubber feet)

## Vinten Service & Support

When you buy **Vinten** a global team of customer service professionals ensures that technical advice, training and service backup is always available. You can also register your product online to receive a **FREE 2 year warranty**.

### Technical Specification

#### Pro-6<sup>HDV</sup> Pan & Tilt head

Type No:	V4018-0001
Capacity:	Maximum 6kg (13.2lb) @ 55mm (2.2") CofG
Weight:	2.2kg (4.8lb)
Tilt Range:	+90° -60°
Pan Range:	360°
Counterbalance:	Selectable 3 steps plus zero
Pan & Tilt Drag:	Infinitely adjustable
Camera Fixing:	Quick attachment and release Sideload system, utilising a standard slide plate complete with 3/8" and 1/4" camera screws with locating pin
Ball Base:	75mm
Levelling Bubble:	Illuminated with low battery indicator
Pan Bar:	Single fixed length

#### Pro-6<sup>HDV</sup>M System

Type No:	Pro-6 <sup>HDV</sup> M
Weight:	7.25kg (16.0lb)
Consisting:	Pro-6 <sup>HDV</sup> head, tripod, mid-level spreader, soft case and multi-lingual operator guide

#### Pro-6<sup>HDV</sup>F System

Type No:	Pro-6 <sup>HDV</sup> F
Weight:	7.35kg (16.2lb)
Consisting:	Pro-6 <sup>HDV</sup> head, tripod, floor spreader, soft case and multi-lingual operator guide

#### Pro-10 Pan & Tilt Head

Type No:	3809-3
Capacity:	10 kg / 22 lbs
Weight:	2.4 kg / 5.2 lbs
Tilt Range:	+90° -60°
Pan Range:	360°
Counterbalance:	Fixed for a 7.5kg / 16.5 lb camera weight
Camera Fixing:	Sliding quick release plate (interchangeable with Vision 3 & 6) with 3/8" and 1/4" screws with locating pin
Ball Base:	75 mm
Levelling Bubble:	Illuminated
Pan Bar:	Single fixed length

#### Pro-10DC System

Type No:	Pro-10DC
Weight:	8.2 kg / 18.1 lbs
Consisting:	Pro-10 head, tripod, spreader, soft case and multi-lingual operator guide

#### PD114 Dolly

Type No:	U005-103
Capacity:	40 kg / 88.2 lbs
Weight:	5.2 kg / 11.5 lbs
Base Diameter:	112 cm / 44.1"
Wheel Diameter:	12.5 cm / 5"

#### Pozi-Loc Tripod

Weight:	3.2 kg / 7lbs
Min Height:	41.6cm / 16.4"
Max Height:	156.2 cm / 61.5"
Transport Length:	71 cm / 28"
Head Fixing:	75 mm bowl

#### Spares and Accessories

12v MN21	Battery (Pro-10)
3v CR1220	Battery (Pro-6 <sup>HDV</sup> )
3330-35	Bowl Clamp
3808-900SP	Camera plate (Pro-6 <sup>HDV</sup> ) incl. 3/8" & 1/4" screws and location pin
3809-900SP	Camera plate (Pro-10) incl. 3/8" & 1/4" screws and location pin
3330-33	Extended length camera plate incl. 2 x 3/8" screws
3219-104	Fixed length pan bar
U005-190	Pro-10 soft system case
U005-190B	Pro-6 <sup>HDV</sup> soft system case
3330-243	75mm ball to 100mm tripod bowl adaptor
3425-3P	Carrying strap incl. fixing kit and instructions